

Electrical Test:

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 2 ohm max.
3. Insulation Resistance: 5M ohm min.
4. Hi-pot:100V DC/10ms

NO	DESCRIPTION	Q'TY	UNIT
10	Label ~85*15MM~synthetic paper ~overglaze ~enhanced sticking ~printing: TECH... CE...	1	pcs
9	Green-base Black-lettered Crystal Glue~9.6*4.5MM~print: Tly	4	pcs
8	TPE~45P~Green (PT:375C	3	g
7	HDMI M Dust cap	2	pcs
6	H.S.T~ ∮1.0MM~Black	0.04	m
5	HDMI A/M 30AWG Clam	2	pcs
4	PVC~45P~Black	15	g
3	LDPE	3	g
2	HDMI A/M 19P Solder insulation:Black shell gold plated pin gold plated	2	pcs
1	[30AWG(7/0.10TC)+EAM]*5P+30AWG(7/0.10TC)*4C+AEB(50%ALMG)+PVC~OD:6.0MM~Color:Black Mark:WWW.TECHLY.COM (← 25.4mm →)HIGH SPEED HDMI? CABLE WITH ETHERNET E342987 兄 AWM STYLE 20276 80℃ 30V VW-1	0.51	M

TOLERANCE	INCHES	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

DRAWN BY
CHECK BY
APPD BY

TITLE: HDMI TO HDMI 30AWG

CUSTOMER : APL
CUSTOMER P/N : ICOC HDMI-4-005

SCALE NONE
UNIT
DATE 2019.09.18

REV. A2

1/2