

Electrical Test:

1. 100%Test(Open ,short ,miss wire)
2. Contact Resistance: 2 ohm max.
3. Insulation Resistance: 10M ohm min.
4. 4*2K/60Hz

Pin Assignment



NO	DESCRIPTION	Q'TY	UNIT
10	white words on black background Label~85*15MM~printing:: TECH...CE...	1	pcs
9	LDPE	4	g
8	45P Black PVC	10	g
7	DisplayPort Port M Clam 28AWG	2	pcs
6	∮1.5 H.S.T 20mm*2pcs	0.04	m
5	DisplayPort M Dust cap	2	pcs
4	DisplayPort M (DP01#) ABS Bottom shell Color:Black	2	pcs
3	DisplayPort M(DP01#) ABS Top shell Color:Black~printing:Tly (Green 376C+White)	2	pcs
2	DisplayPort Port M Solder insulation:Black shell nickel plated pin gold plated	2	pcs
1	DP~[28AWG(7/0.127TC)+EAM]*5P+28AWG(7/0.127TC)*5C+AEB(50%AL)OD:7.3MM~Jacket color:Black~Marking:WWW.TECHLY.COM (← 25.4mm →)DisplayPort Cable E342987 兄 AWM STYLE 20276 80℃ 30V VW-1	2.02	M

REV.	ECN NO.	DESCRIPTION	DATE	NAME

TOLERANCE	INCHES	M/M
.X	.015	.30
.XX	.010	.10
.XXX	.005	.05

TECHly The Modern IT brand

TITLE: DP M TO M DP01# 28AWG 2M

DRAWN BY		CUSTOMER :	ICI
		CUSTOMER P/N :	ICOC DSP-A-020
CHECK BY		SCALE	NONE
		UNIT	MM
APPD BY		DATE	2020.12.08

REV. A1

1/2