

# MINI-DVI ADAPTER REFERENCE GUIDE

MODELS 308489,  
308496 & 308502

Thank you for purchasing this MANHATTAN® Mini-DVI Adapter, Model 308489 (DVI-VGA), 308496 (DVI-DVI-D) or 308502 (DVI-HDMI).

This single-cable solution keeps installations and workplaces neat and orderly — requiring no external power supplies or complicated configuration — making it ideal for training presentations, retail displays, trade events and more. (See back for model specifications.)



*Model 308489:  
DVI-VGA*



*Model 308496:  
DVI-DVI-D*



*Model 308502: DVI-HDMI*

- Delivers a single, high-quality signal from a mini-DVI source to a VGA, DVI-D or HDMI display (as indicated above) – ideal for Mac computers
- Fully shielded to reduce EMI and other interference sources
- Gold-plated connectors provide maximum connectivity
- Molded PVC boot and strain relief
- Lifetime Warranty

  
**MANHATTAN**  
BRINGING COMPUTERS TO LIFE

MANHATTAN® offers a complete line of PC Components, Peripherals, Cables and Accessories. Ask your local computer dealer for more information or visit us online at **[www.manhattan-products.com](http://www.manhattan-products.com)**

Copyright © MANHATTAN

All products mentioned are trademarks or registered trademarks of their respective owners.

MAN-308489/308496/308502-miniQIG-0209-01

# SPECIFICATIONS

## Model 308489: Mini-DVI – VGA

### Standards and Certifications

- UL, DVI

### Contacts

- Mini-DVI-D 32-pin male
- HD 15-pin female
- Gold plated
- Molded PVC boot
- Shielded

### Cable

- 30 and 32 AWG connectors
- Mylar and aluminum shielding
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhms
- Conductive resistance: 10 Ohms
- Thermal plastic casing
- Length: 20 cm (7.9 in.)
- Weight: 31.2 g (1.1 oz.)

## Model 308496: Mini-DVI – DVI-D

### Standards and Certifications

- UL, DVI

### Contacts

- Mini-DVI-D 32-pin male
- DVI-D 24+1-pin female
- Gold plated
- Molded PVC boot
- Shielded

### Cable

- 30 AWG connectors
- Mylar and aluminum shielding
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhms
- Conductive resistance: 10 Ohms
- Thermal plastic casing
- Length: 20 cm (7.9 in.)
- Weight: 45.3 g (1.6 oz.)

## Model 308502: Mini-DVI – HDMI

### Standards and Certifications

- UL, HDMI 1.3, DVI

### Contacts

- Mini-DVI-D 32-pin male
- HD 15-pin female
- Gold plated
- Molded PVC boot
- Shielded

### Cable

- 30 AWG connectors
- Mylar and aluminum shielding
- Withstanding voltage: 300 V DC
- Insulation resistance: 5 MOhms
- Conductive resistance: 10 Ohms
- Thermal plastic casing
- Length: 20 cm (7.9 in.)
- Weight: 25.5 g (0.9 oz.)