



Test Additional

- 1.100% of short circuit and open circuit test & dislocation.
2. The insulation resistance 10M ohm(MIN)
3. The conduction of impedance 2 ohm(MAX).
4. The pressure 300V DC/10ms.

⑩	lack heat shrinkable casing: 1.0 * 13 mm thin wall	0.013	M
⑨	Transparent PE material environmental protection low density	3	g
⑧	45 p start with blue rubber PVC materials and environmental protection	16	g
⑦	Black heat shrinkable casing: 0.8 * 6 mm thin wall	0.024	M
⑥	Black heat shrinkable casing: 2.0 * 7 mm thin wall	0.028	M
⑤	USB 3.0 A(M) After weld line type nickel plating iron shell	1	pcs
④	USB 3.0 A (M) Iron shell plating before welding line	1	pcs
③	USB 3.0(A)F Blue rubber core welding wire type (PT300C) terminals gold-plated 15 u "iron shell plating, G/F.	1	pcs
②	USB 3.0 A(M) 9P Welding line blue rubber core PIN needle gold-plated 5 u	1	pcs
①	UL2725 (28AWG*1P+EAM)*2C+(28AWG*1P+AL)+24AWG*2C+AEB 50%AL OD:5.5 USB 3.0 BLUE (PVC001-6008) 印:E342987 (UL) AWM STYLE 2725 80C 30V VW-1 SUPER HIGH SPEED USB Rev1son 3.0	L	m
NO.	DISCRIPTION	Q'TY	UNIT



USB3.0 Cable AM TO AF

TOLERANCE	INCHES		M/M	SCALE		ICOC U3-AA-XX-EX
	.X	.XX		NONE	MM	
.XXX	.015	.010	.30			DRAWING NO.:
	.005	.10	.10			REV. A
		.05	.05	DATE	14.05.13	1/2